



TIG suvirinimo aparatai



	TransTig 230i	MagicWave 230i	MagicWave 2200	MagicWave 5000
Maitinimo įtampa	230 V	230 V	230 V	400 V
Suvirinimo srovės ribos	3-230 A	3-230 A	3-220 A	3-500 A
Suvirinimo srovė kai: 10 min / 40°C	230 A / 45%	230 A / 35%	220 A / 35%	500 A / 40%
10 min / 40°C	205 A / 60%	195 A / 60%	170 A / 60%	440 A / 60%
10 min / 40°C	170 A / 100%	165 A / 100%	150 A / 100%	350 A / 100%
Apsaugos klasė	IP 23	IP 23	IP 23	IP 23
Svoris	16,4 kg	17 kg	17,4 kg	58,2 kg
Tuščios eigos įtampa	97 V	100 V	88 V	90 V
Darbinė įtampa	10,1 - 19,2 V	10,1 - 19,2 V	10,1 - 24 V	10,1 - 33 V

Hypertherm®

Plazminio pjaušymo aparatai



Plazminio pjaušymo aparatas	Powermax 30 Air	Powermax 45 XP	Powermax 65	Powermax 85	Powermax 125
Tinklo įtampa	230 V	3 x 400 V	3 x 400 V	3 x 400 V	3 x 400 V
Srovės reguliavimo ribos	15 - 30 A	10 - 45 A	20 - 65 A	25 - 85 A	30 - 125 A
Tinklo dažnumas	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz	50 / 60 Hz
Pjovimo gylis: rekomenduojamas	8 mm	22 mm	25 mm	32 mm	44 mm
atskiriamasis	16 mm	24 mm	32 mm	38 mm	57 mm
pradurimas	-	12 mm	16 mm	20 mm	25 mm
Pjovimo srovė / Darbinis ciklas	-	45 A / 40%	65 A / 50%	85 A / 50%	-
Pjovimo srovė / Darbinis ciklas	-	32 A / 100%	46 A / 100%	66 A / 100%	125 A / 100%
Svoris	13,5 kg	15 kg	26 kg	28 kg	65 kg
Matmenys (ilgis x plotis x aukštis)	420 x 195 x 333 mm	442 x 173 x 357 mm	500 x 234 x 455 mm	500 x 234 x 455 mm	592 x 274 x 508 mm
Naudojamo oro slėgis	Įmontuotas kompresorius	5,9 bar	5,9 bar	5,9 bar	5,9 bar
Naudojamo oro srautas		188 l/min	189 l/min	189 l/min	260 l/min