



MIG/MAG suvirinimo pusautomatai



	TransSteel 2200	TransSteel 2700	TransSteel 3500 Compact	TransSteel 5000 Syn
Maitinimo įtampa	230 V	400 V	400 V	400 V
Suvirinimo srovės ribos	10-230 A	10-270 A	10-350 A	10-500 A
Suvirinimo srovė kai: 10 min / 40°C	210 A / 30%	270 A / 30%	350 A / 40%	500 A / 40%
10 min / 40°C	170 A / 60%	210 A / 60%	300 A / 60%	420 A / 60%
10 min / 40°C	150 A / 100%	170 A / 100%	250 A / 100%	360 A / 100%
Apsaugos klasė	IP 23	IP 23	IP 23	IP 23
Svoris	15 kg	29,7 kg	34,6 kg	32,5 kg
Tuščios eigos įtampa	90 V	42 V	59 V	65 V
Darbinė įtampa	14,5 - 24,5 V	14,5 - 34,9 V	14,5 - 38,5 V	14,5 - 39,5 V

MIG/MAG suvirinimo pusautomatai



	TPS 270i C Pulse	TPS 320i C Pulse	TPS 400i	TPS 600i
Maitinimo įtampa	400 V	400 V	400 V	400 V
Suvirinimo srovės ribos	3-270 A	3-320 A	3-400 A	3-600 A
Suvirinimo srovė kai: 10 min / 40°C	270 A / 40%	320 A / 40%	400 A / 40%	-
10 min / 40°C	220 A / 60%	260 A / 60%	360 A / 60%	600 A / 60%
10 min / 40°C	190 A / 100%	220 A / 100%	320 A / 100%	500 A / 100%
Apsaugos klasė	IP 23	IP 23	IP 23	IP 23
Svoris	32,7 kg	35,8 kg	36,45 kg	50 kg
Tuščios eigos įtampa	57 V	71 V	73 V	74 V
Darbinė įtampa	14,2 - 27,5 V	14,2 - 30 V	14,2 - 34 V	14,2 - 44 V

MMA suvirinimo aparatai



	AccuPocket / TIG	TransPocket 150 / TIG	TransPocket 180 / TIG	TransPocket 2500 / TIG
Maitinimo įtampa	Iš baterijos / 230 V	230 V	230 V	400 V
Suvirinimo srovės ribos	150 A	10-150 A	10-180 A	15-250 A
Suvirinimo srovė kai: 10 min / 40°C	150 A / 25%	150 A / 35%	180 A / 40%	250 A / 40%
10 min / 40°C	100 A / 50%	110 A / 60%	150 A / 60%	200 A / 60%
10 min / 40°C	65 A / 100%	90 A / 100%	120 A / 100%	175 A / 100%
Apsaugos klasė	IP 23	IP 23	IP 23	IP 23
Svoris	10,9 kg	6,6 kg	9,0 kg	12,5 kg
Tuščios eigos įtampa	91 V	96 V	101 V	88 V
Darbinė įtampa	0 - 91,0 V	20,4 - 26,0 V	20,4 - 27,2 V	20,6 - 30 V